

METAL CAP OR
COUNTER-FLASHING
(BY OTHERS)

MAXIMUM 12" (305mm)
O.C. FASTENER SPACING **2**

THERMOPLASTIC
CURB WRAP CORNER

APPLICABLE
BONDING
ADHESIVE

12" (305mm)


HOT AIR WELD,
1-1/2" (38mm) MIN.



CUT-EDGE
SEALANT FOR
TPO ONLY **3**

CARLISLE FASTENER
& SEAM FASTENING
PLATE, MAX. 12"
(305mm) O.C. **4**

NOTES:

1. FOUR (4) CURB WRAP CORNERS WILL COMPLETELY FLASH A MAXIMUM CURB SIZE OF 3'X3' (914mmX 914mm). FOR LARGER CURBS USE THE TPO/PVC CURB WRAP CORNERS IN CONJUNCTION WITH ADDITIONAL SECTIONS OF THERMOPLASTIC MEMBRANE.
2. WHEN MECHANICAL FASTENERS ARE USED TO PENETRATE THE METAL COUNTER-FLASHING, USE EPDM WASHERS, APPLY WATER CUT-OFF MASTIC UNDER COUNTER-FLASHING OR CAULK FASTENER HEAD.
3. APPROXIMATELY 1/8" (3mm) BEAD OF CUT-EDGE SEALANT IS REQUIRED ON THE CUT EDGES OF THE TPO FIELD WRAP CORNER.
4. REFER TO CARLISLE SPECIFICATIONS FOR ACCEPTABLE CARLISLE FASTENERS AND PLATES.
5. CUSTOM SIZES ARE AVAILABLE FOR CURB FLASHING HEIGHTS GREATER THAN 12" (305mm).
6. APPLICABLE BONDING ADHESIVE FOR PVC OR TPO. IN CASE OF TPO, CAV-GRIP III ADHESIVE MAY ALSO BE USED ON VERTICAL PORTION.



	● THERMOPLASTIC REINFORCED MEMBRANE
	● APPROVED INSULATION
0	● SEE NOTE(S)

PRE-FABRICATED SURE-WELD TPO
OR SURE-FLEX PVC CURB WRAP
CORNERS

For additional information, refer to Specifications



DETAIL NO.

U-5C

THERMOPLASTIC UNIVERSAL