



PRE-MOLDED INSIDE CORNER BEFORE INSTALLATION

NOTES:

1. POSITION FASTENING PLATES 6" TO 9" (152 TO 229mm) FROM THE CORNER AND 1/2" TO 1" (13 TO 25mm) FROM EDGE OF MEMBRANE.
2. APPROXIMATELY 1/8" (3mm) DIAMETER BEAD OF CUT-EDGE SEALANT IS REQUIRED ON CUT EDGES OF REINFORCED TPO MEMBRANE.
3. REFER TO CARLISLE SPECIFICATIONS FOR ACCEPTABLE CARLISLE FASTENERS AND PLATES.
4. WHEN USING 60 OR 80-MIL MEMBRANE, APPLY A 4-1/2" (114mm) DIAMETER "T-JOINT" COVER AT ALL FIELD SPLICE INTERSECTIONS.

DIMENSIONS	mm	
(A)	6"	152 APPROX.
(B)	6"-9"	152-229
(C)	45-DEGREES APPROX.	

<p>● THERMOPLASTIC REINFORCED MEMBRANE</p> <p>● APPROVED INSULATION</p> <p>0 ● SEE NOTE(S)</p>	<p>PRE-MOLDED INSIDE CORNER FLASHING</p> <p>For additional information, refer to Specifications</p>	<p>DETAIL NO.</p> <p>U-15A</p> <p>THERMOPLASTIC UNIVERSAL</p>
--	---	--