



Roof Access Hatch



Overview

The SunWeld Roof Access Hatch is a self-flashed curbed unit manufactured from 14-gauge painted gray galvanized steel. The curb is 12" in height with a 3½" flange with mounting holes for roof attachment. Custom sizes and curb mount units are available. Available with this unit is the complimentary SunWeld Safety Grab, a railing system that attaches to either corner of the exterior hatch opening. The safety grab, 17" high and extending 10" outward in both directions from the corner, provides improved worker safety for entering and leaving the roof surface.

Features and Benefits

- » All unit components are fully welded at the corners for watertight construction
- » Hinges are two-piece formed steel, with a non-removable, heavy-duty pivot pin
- » The outside cover has radiused corners for safety and is insulated with 1"-thick fiberglass
- » A mechanically bonded EPDM gasket offers a long-lasting weatherproof seal
- » All hardware is corrosion resistant and fasteners are self locking
- » Pre-lubricated compression springs in telescopic tubes ensure smooth operation
- » Interior and exterior handles have provisions for padlocks
- » Hatch is equipped with a vinyl-gripped, hold-open arm

Installation

SunWeld Roof Access Hatches are easy and fast to install. Field-fabricated and factory curbs can be quickly flashed into a roof system using pre-formed TPO or PVC flashing sleeves or EPDM pressure-sensitive curb flashing. All units have pre-drilled installation holes, and special fasteners are provided. No special tools are required.

Review Carlisle specifications and details for complete installation information.

Standard Sizes

- » 30" x 36" and 36" x 36"
- » Limited custom sizes are available

