

MARKETING ANNOUNCEMENT

Authorized Applicator



EPDM-2018-07

20" Sure-White® Pressure-Sensitive Cured Flashing

May 11, 2018

To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is pleased to introduce its 20" Sure-White Pressure-Sensitive (PS) Cured Flashing. Featuring a monolithic 20" of SecurTAPE™, this productivity-boosting accessory can be used for a variety of curb and pipe flashing details. This new product will replace 20" Sure-White PS Curb Flashing (Product Code 309112), which has been discontinued.

Carlisle 20" Sure-White Pressure-Sensitive Cured Flashing	
Product Code	330913
Stocking Locations	Carlisle, PA and Greenville, IL
Packaging	One 20" x 50' roll per carton
Weight	50 lbs per carton
Storage Requirements	Store between 60-90°F (15-32°C)
Product Notes	Sure-White 60-mil cured EPDM with 30-mil SecurTAPE 1-year shelf life Coat curbs with EPDM Primer prior to installation Poly release film is slit 6" in from the edge

Using 20" Sure-White PS Cured Flashing dramatically simplifies the process of completing EPDM target splices under Sure-White Pipe Seals in 30-year systems. Simply clean and prime the deck membrane, cut the 20" flashing to length, peel the release liner, stick the flashing in place, roll, and seal the edges with Lap Sealant. Carlisle's 20" Sure-White PS Cured Flashing is also ideal for use as a target splice when installing EPDM pipe details on mechanically fastened TPO roof systems; additional membrane securement around pipes can now be overlaid with a single piece of flashing instead of four individual pieces.

If you have any questions, or for more information, please contact your Manufacturer's Representative.

Sincerely,

A handwritten signature in black ink that reads "Ronald L. Goodman".

Ronald L. Goodman
EPDM Marketing Manager