## MARKETING ANNOUNCEMENT



**Authorized Applicator** 

EPDM-2018-20 CAV-GRIP™ III for use with EPDM December 7, 2018

## To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is excited to announce that CAV-GRIP III Low-VOC Adhesive/Primer can now be used to bond Sure-Seal®, Sure-Tough®, and Sure-White® EPDM to horizontal substrates for warranty terms up to and including 20-year, 90-mph designs. CAV-GRIP III provides substantial productivity-boosting advantages on the jobsite:

- Can be used in temperatures as low as 25°F (-4°C)
- VOC compliant and very low odor
- Quick application with spray gun
- Fast tack time (< 5 minutes)
- No stirring and easy clean-up
- Up to 60% labor savings compared to traditional bonding adhesive applications

CAV-GRIP III packaging options and supporting accessories are listed below.

<u>Description</u>	Product Code	<u>Packaging</u>	<u>Weight</u>	Stocking Location(s)	Coverage Rate*
CAV-GRIP III	329902	24 per pallet	40 lb	C, G, S, T	1,000 ft <sup>2</sup> *
CAV-GRIP III	332652	12 per pallet	85 lb	Direct Ship	2,000 ft <sup>2</sup> *
Low-VOC UN-TACK	330793	#8 Cylinder	14 lb	C, T	N/A
Spray Gun w/24" Extension**	330912	Box	2 lb	С, Т	N/A
CAV-GRIP 6' Hose	304302	6' length	1 lb	C, G, T, S	N/A
CAV-GRIP 12' Hose	304303	12' length	2 lb	C, G, T, S	N/A
CAV-GRIP 18' Hose	304304	18' length	3 lb	C, G, T	N/A
*Approximate double-sided adhesive application					**Hoses sold separately

CAV-GRIP III has proven to be popular in previously approved applications, including adhering FleeceBACK® EPDM membranes to vertical surfaces, adhering Sure-Weld TPO membranes, and as a primer for VapAir Seal™ 725TR. Contractors who used CAV-GRIP III in the test market have raved about the speed and ease of application, as well as the dramatic reduction in flash-off time. Please give CAV-GRIP III a try on your next adhered project.

If you have any questions, or for more information, please contact your manufacturer's representative.

Sincerely,

Ronald L. Goodman, EPDM Marketing Manager